


VuITnow Multimedia Solutions



This bundled solution for advertising combines a LCD Visual Display monitor and the VuIT Multimedia Communications Module in one package. Display advertisements or other announcements on the crystal clear display monitor through the networkable Multimedia Communications Module. Play video, audio, and music files stored on the module uploaded by a secured network connection. Schedule your files to be played at specific times and play instant messages with the ticker tape feature.

Standard Features:

- Multiple Inputs including 2 x BNC In/Out, 1 x HDMI In, 1 x VGA, 1 x DVI-D, 1 x S-Video In/Out, and 2 x YPbPr
- Picture in Picture, Video over Video, and Picture and Picture
- 3D comb filter, digital noise reduction, and deinterlace provide superior picture quality
- Multimedia Communications Module supports popular video, audio, and photo formats including avi, mpeg, mp3, and jpeg.
- Enhanced network security with site authentication key and SSL secured connection.

Specifications:

	VM-24-10	VM-32-10	VM-42-10	VM-52-10
Screen Size	24"	32"	42"	52"
Viewing Area	20.9" x 11.76" 531.36mm x 298.89mm	27.5" x 15.5" 698.4mm x 392.85mm	36.6" x 20.6" 930.24mm x 523.26mm	45.4" x 25.5" 1152mm x 648mm
Resolution	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
Pixel Pitch	0.27675mm	0.36375mm	0.4845mm	0.6 mm
Brightness	300 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²
Contrast Ratio	1000:1	4000:1	5000:1	5000:1
Viewing Angle (H/V)	170° / 160°	170° / 160°	178° / 178°	178° / 178°
Display Color	16.7 M	16.7 M	16.7 M	16.7 M
Response Time	5.0 ms	6.5 ms	6.5 ms	6.5 ms
Video System	NTSC / PAL BGHI	NTSC / PAL BGHI	NTSC / PAL BGHI	NTSC / PAL BGHI
Frequency (H)	31.5 - 80 KHz	31.5 - 80 KHz	31.5 - 80 KHz	31.5 - 80 KHz
Frequency (V)	56 - 85 KHz	56 - 85 KHz	56 - 85 KHz	56 - 85 KHz
BNC Video In/Out	2 / 2	2 / 2	2 / 2	2 / 2
HDMI In	1	1	1	1
S-Video In/Out	1/1	1/1	1/1	1/1
VGA In / DVI-D In	1/1	1/1	1/1	1/1
YPbPr In	2	2	2	2
VESA Mount Size	VESA 100 x 100	VESA 400 x 200	VESA 400 x 200	VESA 400 x 400
Dimensions	23.8" W x 14.6" H x 3.5" D 603.2 x 370.3 x 90 mm	30.4" W x 18.3" H x 3.8" D 771 x 465 x 96.5 mm	39.6" W x 23.5" H x 4.4" D 1004 x 597 x 111 mm	48.8" W x 29.25" H x 4.2" D 1239 x 743 x 106 mm
Net weight	27.1 lbs (12.3 Kgs)	32 lbs (14.5 Kgs)	55.4 lbs (25.1 Kgs)	106 lbs (48 Kgs)
Gross weight	33.1 lbs (15.0Kgs)	40.4 lbs (18.3 Kgs)	65.7 lbs (29.8Kgs)	119 lbs (54 Kgs)
Regulatory	FCC, CE, UL, RoHS	FCC, CE, UL, RoHS	FCC, CE, UL, RoHS	FCC, CE, UL, RoHS
Power Input	AC 100 ~ 240V	AC 100 ~ 240V	AC 100 ~ 240V	AC 100 ~ 240V
Power Consumption	47W (Max.)	110W (Max.)	165W (Max.)	265W (Max.)
Operating Temperature	32° ~ 104° F (0° ~ 40° C)	32° ~ 104° F (0° ~ 40° C)	32° ~ 104° F (0° ~ 40° C)	32° ~ 104° F (0° ~ 40° C)
Storage Temperature	-4° ~ 140° F (-20° ~ 60° C)	-4° ~ 140° F (-20° ~ 60° C)	-4° ~ 140° F (-20° ~ 60° C)	-4° ~ 140° F (-20° ~ 60° C)
Supported Video	AVI, VOB, MPEG 1/2/4, DivX, WMV, TS			
Supported Audio	Mp3 / WAV / AAC / WMA			
Supported Photo	Bmp / Jpg / Jpeg / Png /Gif			
Security	Site authentication key and SSL secured connection			

VuIT Communications, LLC

Phone: (480)563-8064

www.vuitcommunications.com

Specifications subject to change without notice

©2010 VuIT Communications LLC
All rights reserved

VuITnow
FOR ADVERTISING